2', 3', 4.25' and 5.5' cone crushers, on support legs

Triaso general characteristics in these cone crushers on support legs

- Heavy duty design and materials.
- Industrial design, focused on aesthetics to favor your company´s image.
- Mining specifications: 100% operation cycle under highly contaminated environment.
- Siemens™ motors and electrical parts.
- Electric system: Cables, starters, cabinets, ducts, connectors, etc.
- Heavy duty cabling, polarized to ground motors.
- Quick connection contacts, with indicative signs and protection against weather.
- Conveyor and hopper manufactured under strict Cema-6 specifications.
- Conveyor capable to start up fully loaded with material.
- Belt vulcanized at the jointures (without clamps), for longer durability and smoother operation.
- Power transmission with extra sized heavy duty Browning™ gear reductors.
- Power transmissions with hub mounted steel pulleys.
- Heavy duty idlers, with bearings sealed against water and dust.
- Heavy duty mounted bearings sealed against water and dust.
- Galvanized screws for longer life, easier unscrewing and oxide stains elimination.
- High quality electrostatic automotive paint (baked) in medium to small size pieces.
  - High corrosion-resistance, high adherence and long lasting color.
- Security elements as well as pertinent warnings to protect the equipment and your personnel.

Symons type cone, short or standard head, with several cavitys available: Fine, medium, coarse and extra coarse


- 2'.
- 3'.
- 4.25'.
- 5.5'.

Bowl locking system:

- Locking thru hydraulic jacks.
- Cavity opening and closing thru hydraulic jacks.
- Operation console with integrated oil tank.
- High pressure oil pump with electric motor.
- Adjustable range of locking pressure, for automatic operation of the pressure pump.

Clearing system, to release the crushing cavity:

- Independent high pressure pump, with electric motor.
- Release thru hydraulic jacks to raise the bowl.



Motor

- 30 Hp in the 2' cone.
- 100 Hp in the 3' cone
- 200 Hp in the 4.25' cone.
- 300 Hp in the 5.5' cone.

Catwalk for inspection, with railings and ladder

Conveyor under the cone

- 18" width with 3 Hp motor in the 2' cone.
- 24" width with 5 Hp motor in the 3' cone.
- 30" width with 5 Hp motor in the 4.25' cone.
- 36" width with 5 Hp motor in the 5.5' cone.

Lubrication system:

- Lubrication pump with electric motor.
- Pressure and flow sensor with automatic stoppage due to lack of lubrication.
- Lubrication oil cooler, with electric ventilator.
- Lubrication oil heater, thru electric resistances.
- Lubrication oil temperature sensor.
- Automatic temperature control to activate cooler or heater for the lubrication oil.
- Lubrication oil tank.
- Level sensor for lubrication oil to allow start up or automatic stop.
- Valves for security and pressure regulation of lubrication oil.
- Control cabinet with Siemens electric parts and Parlow thermometers.

In-work support legs, with predetermined height for a quick installment